

Reversible Module

Optical Breakout - 12 channels (multimode)

XVVRM-OBO12M



● Fiber ——— (D) destination point



The Optical Breakout - 12 channels (multimode) Reversible Module fits in the Theatrixx 8-bay Frame.

The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. It is a fully passive module requiring no external power, and allows combining 4 optical signals into a single cable, allowing trunking applications. Video, network, audio and more can all be combined in a single cable!

Specifications

Supported Signals

Multi-Core Connector	1 x OpticalCON MTP
Single Connectors	12 x ST

Physical Specifications

Height	121.5 mm (4.78 in)
Depth	225 mm (8.85 in)
Width	41 mm (1.61 in)
Weight	710 g (1.56 lbs)

Environmental Specifications

Relative Humidity	0% to 90% non-condensing
Operating Temperature	0-40 °C

Power Requirements

Power Consumption	None (Passive)
Voltage Range	None (Passive)

In the Box

Theatrixx Reversible Module Optical Breakout - 12 channels (multimode)

Certifications & Compliance

This device complies with the following international standards



Ordering Information

XVVRM-OBO12M	Theatrixx Reversible Module Optical Breakout - 12 channels (multimode)
XVVRF8	Theatrixx 8-Bay Frame
XVVRM-BLANK	Theatrixx Blank Module