

DCNM-ENCS Electronic name card single sided DICENTIS



- ► Single-sided E-ink display to show participant name and organization logo
- ▶ Very low power consumption
- Easily managed and updated

The DCNM-ENCS can display the participant name and the organization logo. This single-sided electronic name card reduces effort and saves time by replacing paper name cards.

It is easily managed and automatically updated by the DICENTIS system. The electronic name card can be connected to a seat to display the name of a participant. If free seating is available and the participant logs in at another seat, it updates automatically.

The electronic name card is easily integrated with the DICENTIS topology. It can be daisy-chained with the DICENTIS cable or star-wired via PoE.

Functions

General

- Single-sided E-ink display.
- · Supports star and loop-through connection.

Security

 Encryption ensures that information within the system remains confidential.

Controls

 A link button is mounted on the base to make pairing easy.

Interconnections

- 2x RJ45 compatible connection for system communication and power.
- · Hot Plug-and-play.

Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

Parts included

Quantity	Component
1	DCNM-ENCS Electronic name card single sided

Technical specifications

Electrical

Input voltage (VDC)	48 VDC
Power consumption (W)	2 W

Flush-mounted; Tabletop (if com-

bined with the DCNM ENCE

Mechanical

Mounting type

	bined with the DCNM-ENCF)	
Dimensions for flush-mounting		
Dimensions (H x W x D) (mm)	158 mm x 384 mm x 40 mm	
Dimensions (H x W x D) (in)	6.2 in x 15.1 in x 1.6 in	
Dimensions (W x D) (display)	325 mm x 21.5 mm	
Dimensions (W x D) (display)	12.8 in x 8.5 in	
Dimensions for tabletop mounting (with DCNM-ECNF)		

Dimensions (H x W x D) (mm)	188 mm x 325 mm x 54 mm
Dimensions (H x W x D) (in)	7.4 in x 12.8 in x 2.1 in
Width (mm) (foot)	304 mm
Width (in) (foot)	12 in
Depth (mm) (display)	21.5 mm
Depth (mm) (display)	8.5 in

Environmental

Operating temperature (°C)	5 °C − 45 °C
Operating temperature (°F)	41 °F – 113 °F
Storage temperature (°C)	-30 °C - 70 °C
Storage temperature (°F)	-22 °F − 158 °F
Operating relative humidity, non- condensing (%)	5% - 90%

Ordering information

DCNM-ENCS Electronic name card single sidedElectronic name card with single-sided E-ink display.
Order number **DCNM-ENCS | F.01U.385.665**

Accessories

DCNM-ENCF Electronic name card foot

Electronic name card foot for tabletop mounting. Order number **DCNM-ENCF | F.01U.428.416**

