

DCNM-FBD2 Flush base device 2

DICENTIS



- ▶ Standard 2 participants mode
- ▶ Possible to make 4 participant positions with shared microphones and loudspeakers
- ▶ Loop through with a DICENTIS cable

The Flush base device 2 is intended for use in flush mounted solutions. It enables the addition of a number of functions, making it suitable for chairpersons and participants. Each input can be assigned its own seat number, allowing the DCNM-FBD2 to serve two participant positions. With the dual use license you can increase the maximum participant positions to 4, with each position sharing their microphone and loudspeaker.

Functions

- The DCNM-FBD2 creates flush-mounted positions with the Flush panels.
- The device can be mounted under the under tabletops or in the arm rests of chairs.
- It enables loop-through to other Flush base device.
- The device has two audio inputs which connect to two DCNM-FMCP when a DICENTIS Flush microphone is used.
- The green/amber LED indicates the unit status.

Interconnections

- Two RJ12 connectors to connect button modules. Each connector serves one participant, but multiple modules, like DCNM-FMICB and DCNM-FPRIOB, can be daisy-chained on one port.
- Two balanced audio inputs to connect a DCNM-FMCP (3 pole terminal block).
- Two RJ45 compatible connectors for system communication and power.
- Two loudspeaker outputs to connect a DCNM-FLSP (2 pole terminal block).

Parts included

Quantity	Component
1	DCNM-FBD2 Flush base device 2
1	Quick installation guide
1	Anti-take out bracket
2	2 m CAN cable
2	30 cm CAN cable

Technical specifications

Electrical

Operating voltage (VDC)	48 VDC
Power consumption (W) (FBD only)	5 W
Power consumption (W) (with modules)	Refer to the Power Calculation tool

Mechanical

Mounting type	Wall-mounted, under a tabletop or seat, in an arm rest or cable duct
Dimensions (H x W x D) (mm) (excl. cables)	32 mm x 100 mm x 200 mm
Dimensions (H x W x D) (in) (excl. cables)	1.26 in x 3.90 in x 7.90 in

Weight (g)	656 g
Weight (lb)	1.45 lb
Color in RAL	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Operating temperature (°C) (enclosed in a duct)	5 °C – 35 °C
Operating temperature (°F) (enclosed in a duct)	41 °F – 95 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FBD2 Flush base device 2

Flush mounted base device.

Order number **DCNM-FBD2 | F.01U.405.788**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com