

# DCNM-FIDP Flush identification panel

## DICENTIS



The DCNM-FIDP supports fast participant recognition through NFC-tag identification. Identification allows for attendance registration and authorization of the participant in the meeting. After identification, the authorizations and headphone language of the participation are set for security and ease of use. The device detects ID cards between 0 and 1 cm away to prevent unintended identification.

### Functions

- Supports identification cards.
- 4 Flush identification panels can be connected to a DCNM-FBD2 in dual use mode.

### Interconnections

- Control interface, through RJ12, to the DCNM-FBD2 and other devices.

### Parts included

Quantity	Component
1	DCNM-FIDP Flush identification panel
1	30 cm cable

### Technical specifications

#### Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
---------------	---

- ▶ Also available in customized colors, wood, stone or metal designs
- ▶ Near-field communication card reader to identify participant
- ▶ Lighted icon guides the user
- ▶ Optional card holder
- ▶ Icon on only when the functionality is available to prevent distractions

Dimensions (H x W x D) (mm)	56 mm x 50 mm x 34 mm
Dimensions (H x W x D) (in)	2.20 in x 1.97 in x 1.34 in
Weight (g)	35 g
Weight (lb)	0.08 lb
Color (RAL)	RAL 9017 Traffic black

#### Electrical

Power consumption (W)	0.50 W
Operating voltage (VDC)	5 VDC

#### Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

## Ordering information

### DCNM-FIDP Flush identification panel

Flush-mounted identification panel.

Order number **DCNM-FIDP | F.01U.402.925**

## Accessories

### DCNM-FICH Flush ID card holder

ID card holder for the participant to automatically login when the card is parked and logout when it is removed.

Order number **DCNM-FICH | F.01U.402.928**

## Software Options

### DCNM-LSID License for identification at 1 seat

DICENTIS software license for enabling identification at seat in the DICENTIS Discussion device with voting, DICENTIS Discussion device with language selector, DICENTIS Discussion device with touchscreen, DICENTIS Multimedia device, and DICENTIS wireless Extended.

Order number **DCNM-LSID | F.01U.300.533**

#### Represented by:

##### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

##### Germany:

Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Platz 1  
D-70839 Gerlingen  
[www.boschsecurity.com](http://www.boschsecurity.com)

##### North America:

Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
[www.boschsecurity.com](http://www.boschsecurity.com)

##### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)