

DCNM-FMCP Flush microphone connection panel

DICENTIS



The Microphone connection panel connects the pluggable microphones DCNM-MICSLS and DCNM-MICSL to one of the audio inputs of the Flush base device (DCNM-FBD).

The shock-mount principle reduces unwanted sound from tables going into the microphone. The microphone connection panel has a pre-amplifier for the microphone while maintaining GSM immunity and control over the microphone LEDs.

Functions

Interconnections

- Balanced audio interface to connect to the DCNM-FBD (2 m cable with a 3 pole terminal block).
- Power and control interface to the DCNM-FMICB/DCNM-FPRIOB.

Parts included

Quantity	Component
1	DCNM-FMCP Flush microphone connection panel
1	Power cable
1	Audio cable

Technical specifications

Electrical

Frequency response (-3 dB) (Hz) (-3 dB at nominal level)	125 Hz – 15,000 Hz
---	--------------------

- ▶ Also available in customized colors, wood, stone or metal designs
- ▶ Stylish and modern design
- ▶ Shock-mount technology for less external noise
- ▶ The microphone and loudspeaker can be active at the same time
- ▶ Sturdy connection to the microphone

Total harmonic distortion + noise (%)	0.10%
Dynamic range (dB)	90 dB
Minimum signal-to-noise ratio (dB)	90 dB

Microphones

According to ISO 22259

Nominal acoustic input level (dB SPL)	80 dB SPL
Maximum acoustic input level (dB SPL)	110 dB SPL

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions (H x W x D) (mm)	56 mm x 50 mm x 80 mm
Dimensions (H x W x D) (in)	2.20 in x 2 in x 3.10 in
Weight (g)	70 g
Weight (lb)	0.20 lb
Color (RAL)	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FMCP Flush microphone connection panel

Flush mounted microphone connection panel.

Order number **DCNM-FMCP | F.01U.383.837**

Services

EWE-DCNMFP-IW 12 mths wrty ext DICENTIS Flush Panel

12 months warranty extension

Order number **EWE-DCNMFP-IW**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com