

DCNM-FVP Flush voting panel

DICENTIS



The Flush voting panel has five capacitive buttons: Present, For, Against, Abstain and DNPV. The DCNM-FVP connects to DCNM-FBD2 Flush base device for power and control.

Functions

General

- Five color-coded touch buttons distinguish the voting options:
 - Blue:** Present button
 - Green:** For / A
 - Red:** Against / B
 - Yellow:** Abstain / C
 - Orange:** DNPV / D

Interconnections

- Control interface, through RJ12, to the DCNM-FBD2 and other devices.

Parts included

Quantity	Component
1	DCNM-FVP Flush voting panel
1	30 cm cable

Technical specifications

Electrical

Power consumption (W)	0.50 W
-----------------------	--------

- ▶ Also available in customized colors, wood, stone or metal designs
- ▶ Five touch buttons for different voting options
- ▶ Optimal user experience
- ▶ The voting buttons are only illuminated when the functionality is available to avoid distraction

Operating voltage (VDC)	5 VDC
-------------------------	-------

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions (H x W x D) (mm)	56 mm x 100 mm x 34 mm
Dimensions (H x W x D) (in)	2.20 in x 3.94 in x 1.34 in
Weight (g)	62 g
Weight (lb)	0.14 lb
Color (RAL)	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F

Operating relative humidity, non-condensing (%)	5% – 90%
---	----------

Ordering information

DCNM-FVP Flush voting panel

Flush-mounted voting panel.

Order number **DCNM-FVP | F.01U.402.924**

Software Options

DCNM-LSVT License for voting at 1 seat

DICENTIS software license for enabling voting at seat in the DICENTIS Multimedia, DICENTIS Discussion device with touchscreen, and DICENTIS wireless Extended. The DICENTIS Discussion device with voting has the functionality built-in.

Order number **DCNM-LSVT | F.01U.300.532**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com