

DCNM-FHHC Hand held microphone coiled

DICENTIS



The DCNM-FHHC is an uni-directional, condenser microphone with built-in pop and windshield. It comfortably fits into one hand and includes a button for control.

The Flush hand held microphone coiled is installed in participant seats without space for a tabletop or flush-mounted device. It can also create a floor-stand microphone position.

It is possible to connect the DICENTIS Flush hand held microphones to the DCNM-FAI. With two DCNM-FAI, two of these microphones can be connected to the Flush base device 2.

Functions

- Connects to the DCNM-FAI to become part of the DICENTIS system.
- Condenser microphone with built-in pop and windshield.
- Microphone request-to-speak button.
- Red LED: Microphone on.
- Green LED: Request-to-speak confirmation.

Parts included

Quantity	Component
1	DCNM-FHHC Hand held microphone coiled

Technical specifications

Audio

Bandwidth (Hz)	125 Hz – 15.000 Hz
Dynamic range (dB)	100 dB

- ▶ Creates a floor-stand microphone position when table space is limited
- ▶ 1.5 m cable (when uncoiled)
- ▶ Built-in pop and windshield
- ▶ Request-to-speak button and LED status indicators

Nominal acoustic input level (dB SPL)	85 dB SPL
Maximum acoustic input level (dB SPL)	115 dB SPL
Self noise (dB SPL)	15 dB SPL

Mechanical

Cable length (m)	1.5 m (when uncoiled)
Cable length (ft)	4.9 ft (when uncoiled)
Color in RAL	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	-22 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 95%

Ordering information

DCNM-FHHC Hand held microphone coiled

Flush hand held microphone with a cable of 1.5 m (4.9 ft) of length (when uncoiled).

Order number **DCNM-FHHC | F.01U.405.508**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:

Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com